



CARUSO

CODIGO: FP7000CEILING FAN

CARUSO CELING FAN

- **INSTALLATION REQUIREMENTS:** Fan must be secured to a structural member, such as a ceiling joist, capable of withstanding a load of at least 100 lbs. A 3/8" x 5" long lag bolt passes through loop in ceiling support cable, hanger bracket plate, and into wood structural member above.
- **ELECTRICAL REQUIREMENTS:** Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit
- **MOTOR SPECS:** Powerful twin 188 x 25 motors are designed for optimal performance with this fan.
- **FAN SPEEDS:** 2-speed reversible (located on switch cup).

Fan Speed	Airflow	Electricity Use	Max. RPM	Airflow Efficiency
Low	8,293 cfm	90.8 w	95	70 cfm/w
High	6,335 cfm	146 w	127	57 cfm/w

- **DESIGN FEATURES:** Adjustable motor heads with five angles of blade tilt; Vertical, 15°, 30°, 45°, and 60° from vertical.
- **BLADES:** A variety of palm, bamboo, and all-weather composite blades are available—sold separately. See chart on page 28, or our
- **CONTROL OPTIONS:** CW3WH-CA 2-speed wall control is included. Optional TR24 hand-held remote control is available with the use of optional SW70 switch cap receiver— sold separately. Instructions are provided with each control.